

# TOWARDS A STANDARDIZED BOND TEST FOR ON-SITE STRUCTURAL CONCRETE QUALITY CONTROL

Michel LORRAIN, professor  
Department of Civil Eng., INSA Toulouse  
LaSaGeC<sup>2</sup>, UPPA

michel lorrain, 2009

1

## SUMMARY

- About quality control...
- What is done nowadays?
- What else could be done?
- First results
- Conclusions and future prospects

michel lorrain, 2009

2

## 1 - ABOUT QUALITY CONTROL...

- Modern societies aim at the « zero risk» level of safety
- Laws protect the consumer and give insurance companies the means to insure building works
- Based on quality control more and more exacting...

michel lorrain, 2009

3

## A compulsory stage... advantages

- Verification that actual material properties are conform to the design requirements
- Protection against important damage
- Planning optimization and potential savings

michel lorrain, 2009

4

## However a limited efficiency...

- Serious damage, deadly sometimes, occurs too frequently
- Requirements are not always easy to fulfill
- Costs tend to increase...

michel lorrain, 2009

5

## 2 - THE PRESENT WAY TO ASSESS CONCRETE STRENGTH: THE AXIAL COMPRESSION TEST

- Since the French « circulaire de 1906 », structural concrete quality control is assessed through axial compression tests
- With changing experimental processes...cube, cylinder,...
- Implementation is ruled by precise standards

michel lorrain, 2009

6

## European regulations for Testing hardened concrete under compression

- **NF EN 12390-1 to 4** October 2001 - P 18-430
- Éditée et diffusée par l'Association Française de Normalisation (AFNOR) — ICS : 91.100.30
- **Part 1:** Shape, dimensions and other requirements for test specimens and moulds
- **Part 2:** Making and curing specimens for strength tests
- **Part 3:** Compressive strength of test specimens
- **Part 4:** Specifications for testing machines

Michel Lorrain, 2009

7

## Some obvious advantages of the concrete compression test

- The test seems easy to perform and easy to interpret
- The result of the test is directly implemented in structural calculations
- The concrete compression strength is strongly correlated to the other mechanical properties

Michel Lorrain, 2009

8

## Some obvious drawbacks of the concrete compression test

- The test is not so easy to interpret, the result is conventional
- The test is not so easy to perform: with increasing performance of concrete, failure strength increases
- Testing devices are sophisticated
- Specimens have to be prepared carefully

michel lorrain, 2009

9

## As a conclusion about the concrete axial compression test

- Doesn't have exceptional properties
- Nothing gives any justification of its exclusiveness as THE mechanical reference
- Is not intrinsically compulsory...what engineers need is data for calculations and quality certification

michel lorrain, 2009

10

### 3 - THE BOND TEST AS AN ALTERNATIVE TO THE CONCRETE COMPRESSION TEST

- Well known and performed since the beginning of reinforced concrete construction
- Dedicated to certify the efficiency of strength transfer in the composite constitution of reinforced concrete

michel lorrain, 2009

11


### Bond test: the ways to perform

- Different ways can be used: pulling out, pushing out, bending « beam-test », etc.
- There is not yet a standard test, but some recommendations ASTM, RILEM CEB/FIP (P.O.T on 20cm cube) exist


michel lorrain, 2009

12

# The RILEM recommendations



# The typical result of bond tests



micHEL lorraine, 2009

## Some obvious drawbacks of the bond test

- Sometimes difficult to perform
- Experimental procedures are numerous
- Results depend on concrete strength AND on bar roughness
- Said to be scattered

Michel Lorrain, 2009

15

## Some obvious advantages of the bond test

- It is a composite material test
- Only inferior strength has to be applied
- There is a strong correlation between bond strength and concrete compression strength

Michel Lorrain, 2009

16



Building codes use these relationships to assess bond strength from concrete quality

$$\tau_{su} = 0,6 \cdot \psi_s^2 \cdot f_{tj}$$

$$f_{bd} = (2.25 f_{ctk0.05}) / \gamma_c$$

$$f_{bd} = \eta_1 \cdot \eta_2 \cdot \eta_3 \cdot f_{ctd}$$

michel lorrain, 2009

17


## As a conclusion about the Bond Test

- Can also provide data for calculations and concrete quality certification
- Not less reliable than the concrete compression test... if performed in an appropriate way
- There is no reason not to consider an appropriate bond test as a standard for concrete quality

michel lorrain, 2009

18

## An appropriate Pull Out Test



michel Iorrain, 2009

19

## Experimental investigation for the definition of the specimen features



Moncef MAKNI<sup>1</sup>; Atef DAOUD<sup>2</sup>; Michel LORRAIN<sup>3</sup>; Mohamed Ali KARRAY<sup>4</sup>

<sup>1</sup> ISET Sfax BP 88-A, 3099 El Bustan ; Laboratoire de Génie Civil (LGC) ENIT BP 37, 1002 Tunis, TUNISIE

<sup>2</sup> ENIG Gabès ; Laboratoire de Génie Civil (LGC) ENIT BP 37, 1002 Tunis, TUNISIE

<sup>3</sup> INSA Toulouse ; LaSaGeC ISA-BTP Anglet, FRANCE

<sup>4</sup> ENIT Tunis ; Laboratoire de Génie Civil (LGC) ENIT BP 37, 1002 Tunis, TUNISIE

N° de l'éprouvette	Diamètre de l'éprouvette (mm)	$c/\phi_s$	$F_{max}$ (N)	Mode de rupture
S211	69	2,875	25260	Fendage longitudinal du béton
S212	69	2,875	25140	Fendage longitudinal du béton
S213	69	2,875	24550	Fendage longitudinal du béton
S221	94	3,916	37710	Fendage longitudinal du béton
S222	94	3,916	37050	Fendage longitudinal du béton
S223	94	3,916	38240	Fendage longitudinal du béton
S1	119,6	4,985	31160	Arrachement de la barre d'acier
S2	119,6	4,985	34950	Arrachement de la barre d'acier
S3	119,6	4,985	37180	Arrachement de la barre d'acier
S231	134	5,583	32920	Arrachement de la barre d'acier
S232	134	5,583	35630	Arrachement de la barre d'acier
S233	134	5,583	30570	Arrachement de la barre d'acier
S241	159,6	6,650	35890	Arrachement de la barre d'acier
S242	159,6	6,650	31560	Arrachement de la barre d'acier
S243	159,6	6,650	34400	Arrachement de la barre d'acier

michel lorrain, 2009


21

Slenderness is not enough...not removing  
the form has been found a good thing

**Béton C25/30**

N° EP	$REp/\phi_s$	$F_{max}$ KN	Mode de rupture
S51	2,875	22,02	ECLATEMENT TYPE FRAGILE SANS CISAILLEMNT DE LA ZONE D'INTERFACE
S52	2,875	27,26	ECLATEMENT TYPE FRAGILE SANS CISAILLEMNT DE LA ZONE D'INTERFACE
S53	2,875	18,42	ECLATEMENT TYPE FRAGILE SANS CISAILLEMNT DE LA ZONE D'INTERFACE
S41	3,916	34,27	ECLATEMENT TYPE FRAGILE SANS CISAILLEMNT DE LA ZONE D'INTERFACE
S42	3,916	38,04	ECLATEMENT TYPE FRAGILE SANS CISAILLEMNT DE LA ZONE D'INTERFACE
S43	3,916	37,35	ECLATEMENT TYPE FRAGILE SANS CISAILLEMNT DE LA ZONE D'INTERFACE
S31	4,985	33,38	ECLATEMENT + CISAILLEMNT DE LA ZONE D'INTERFACE
S21	5,583	42,52	ECLATEMENT + CISAILLEMNT DE LA ZONE D'INTERFACE
S22	5,583	45,05	ECLATEMENT + CISAILLEMNT DE LA ZONE D'INTERFACE
S23	5,583	38,19	ECLATEMENT + CISAILLEMNT DE LA ZONE D'INTERFACE
S11	6,65	43,2	ECLATEMENT + CISAILLEMNT DE LA ZONE D'INTERFACE
S12	6,65	52,12	ARRACHEMENT DE LA BARRE D'ACIER


Bond tests if not performed in an appropriate way are scattered and not reliable



Michel Lorrain, 2009

23


A strong correlation between bond strength and concrete compression strength



Michel Lorrain, 2009

24


### A strong correlation between bond strength and concrete compression strength



Michel Lorrain, 2009

25

### Directions for use to assess concrete quality from bond strength



Michel Lorrain, 2009

26

## 6 - FIRST RESULTS OF A FEASIBILITY STUDY

- To check technical feasibility under on-site conditions
- To check easiness to perform, reliability and cheapness

michel lorrain, 2009

27

## An experimental procedure for on-site tests

- Specimen molded in the plastic shell of mineral water bottles,  $\Phi$  8 cm, with  $\phi$  8 mm max. steel rebar (cf. RILEM –CEB/FIP and Daoud/Makni ENIT 2009)
- Bonded length varying from 8 to 12 cm

michel lorrain, 2009

28

















## The first results...

- P.O.T on « bottled » specimen 7 to 14 days old, rebar diameters varying  $\phi 6$ ,  $\phi 8$  mm,  $\sigma_{bc28}$  around 40 MPa, bonded length 8 cm, were performed in INSA Toulouse (France) and ENI Gabès (Tunisia)
- Observed:
  - \* no splitting failure
  - \* always bond-slip failure
  - \* standard-deviation: 0,5 MPa

micHEL lorrain, 2009

41


## Fitting with previous correlation curves



micHEL lorrain, 2009

42

## Fitting with previous correlation curves



michel lorrain, 2009

43

## CONCLUSIONS

- Both quality control and structural calculations are concerned by concrete compressive strength
- Bond strength also has to be checked to insure efficient force transfer inside the composite
- All this data can be given through a single bond test, appropriate P.O.T for instance, easy to perform, cheap, reliable and available on-site.

michel lorrain, 2009

44

## FUTURE PROSPECTS

To meet the compulsory requirements for standardization, further research must be developed :

- FEM study to confirm the specimen features
- Experimental intensive investigation in different places with different concrete and deformed bars to enable statistical processing

Michel Lorrain, 2009

45

## THANK YOU FOR ATTENTION

Michel Lorrain, 2009

46

